

Magnetic Contactors And Auxiliary Switches



Features

Contactors meet UL508 specifications for devices up to 600 VAC.

- 50/60 Hertz • CULUS approved
- Coils have class B insulation
- Includes Lug, spade terminals, and covers



Item ID	Poles	F/L	Locked	Resistive Amps	Coil Voltage	Notes
		Inductive Amps	Rotor Amps 240/480/600			
1 Pole						
C125A	1	25	150/125/100	30	24	
C125B	1	25	150/125/100	30	120	
C125C	1	25	150/125/100	30	208/240	
C130A	1	30	180/150/120	40	24	
C130B	1	30	180/150/120	40	120	
C130C	1	30	180/150/120	40	208/240	
C140A	1	40	200/160/120	50	24	
C140B	1	40	200/160/120	50	120	
C140C	1	40	200/160/120	50	208/240	

2 Pole

NEW	C220A	2	20	120/100/80	30	24	
NEW	C220B	2	20	120/100/80	30	120	
NEW	C220C	2	20	120/100/80	30	208/240	
	C225A	2	25	150/125/100	35	24	
	C225B	2	25	150/125/100	35	120	
	C225C	2	25	150/125/100	35	208/240	
	C230A	2	30	180/150/120	40	24	
	C230B	2	30	180/150/120	40	120	
	C230C	2	30	180/150/120	40	208/240	
	C230D	2	30	180/150/120	40	208/240	555
	C240A	2	40	200/160/120	50	24	
	C240B	2	40	200/160/120	50	120	
	C240C	2	40	200/160/120	50	208/240	

Notes:

555. Spade terminals and cover only.

Item ID	Poles	F/L	Locked	Resistive Amps	Coil Voltage
		Inductive Amps	Rotor Amps 240/480/600		
3 Pole					

NEW	C325A	3	25	150/125/100	35	24
NEW	C325B	3	25	150/125/100	35	120
NEW	C325C	3	25	150/125/100	35	208/240
	C330A	3	30	180/150/120	40	24
	C330B	3	30	180/150/120	40	120
	C330C	3	30	180/150/120	40	208/240
	C340A	3	40	240/200/160	50	24
	C340B	3	40	240/200/160	50	120
	C340C	3	40	240/200/160	50	208/240
	C350A	3	50	300/250/200	65	24
	C350B	3	50	300/250/200	65	120
	C350C	3	50	300/250/200	65	208/240
	C360A	3	60	360/300/240	75	24
	C360B	3	60	360/300/240	75	120
	C360C	3	60	360/300/240	75	208/240
	C375A	3	75	450/375/300	90	24
	C375B	3	75	450/375/300	90	120
	C375C	3	75	450/375/300	90	208/240
	C390A	3	90	540/450/360	120	24
	C390B	3	90	540/450/360	120	120
	C390C	3	90	540/450/360	120	208/240

4 Pole

	C430A	4	30	180/150/120	40	24
	C430B	4	30	180/150/120	40	120
	C430C	4	30	180/150/120	40	208/240
	C440A	4	40	240/200/160	50	24
	C440B	4	40	240/200/160	50	120
	C440C	4	40	240/200/160	50	208/240

Magnetic Contactor



Item ID	C18001
Type	DPST N.O.
Resistive Amps	30
Full Load Amps	30
Locked Rotor Amps	120
Coil Voltage	24
Hertz	50/60
Maximum Surrounding Air Temperature	40 °C
Phase	Single

Replaces

GE 3ARR8E4 GEM MC11
Mars 18001 WR/Essex/RBM 90-230

Auxiliary Switches



Item ID	Type	Amps
Packard		
P6S	SPDT	30-40
P7S	SPDT	30-40
P8S	SPDT	50-60
P9S	SPDT	70-90
MI1	Mechanical Interlock	20-40
AC3	NDNC	20-60
NEW P38K	Includes P8S and AC3	